



NEW FROM SOLAX X3-FIT G4



X3-FIT G4
6kW/8kW/10kW/15kW

Features

High-efficient

- Up to 110% AC overload output
- Higher efficiency on charging and discharging, up to 98.5%

Economic

- Store the surplus energy to battery
- Less energy loss on battery to inverter

Intelligent

- 150% EPS output, 10s
- Switchover time <10ms
- Quick configuration with U-disk
- Lithium-ion & Lead-acid battery compatible
- Intelligent loads management (e.g., Heat pump)
- On & Off-grid parallel function, up to 150kW
- 5 work modes, 2 charging periods available
- VPP ready, ancillary service in power market
- Three-phase unbalanced output Maximum 5kW output power on single phase at most

Safe

- IP65 protection level
- Integrated SPD

Contact Us for More Informations

www.solaxpower.com

AU: +61 1300 476529

DE: +49 6142 4091664

OneHeat
solenergi & värme

info@solaxpower.com
service@solaxpower.com



	X3-FIT-6.0-W	X3-FIT-8.0-W	X3-FIT-10.0-W	X3-FIT-15.0-W
AC INPUT & OUTPUT				
Nominal AC output power [W]	6000	8000	10000	15000
Max. AC output apparent power [VA]	6600	8800	11000	15000
Max. AC output current [A]	9.7	12.9	16.1	24.1
Max. AC input apparent power [VA]	12000	16000	20000	20000
Max. AC input current [A]	19.3	25.8	32	32
Nominal AC voltage [V]	380 / 220; 400 / 230; 415 / 240			
Nominal grid frequency [Hz]	50 / 60			
Displacement power factor	0.8 leading ~ 0.8 lagging			
THDi (rated power) [%]	< 3			
BATTERY DATA				
Battery type	Lithium-ion battery / Lead-acid Battery			
Battery voltage range [V]	180 ~ 800			
Max. continuous charge/discharge current [A]	30			
EPS(OFF-GRID OR BACK-UP) OUTPUT (WITH BATTERY)				
Nominal output power [W]	6000	8000	10000	15000
Peak apparent power [VA, s]	12000, 10s	18000, 10s	18000, 10s	22500, 10s
Max. continuous current [A]	8.7	11.6	14.5	21.8
Nominal voltage [V]; Frequency [Hz]	400 / 230; 50 / 60			
Switch time [ms]	< 10			
Parallel operation	YES			
SYSTEM DATA				
Max. efficiency [%]	98.0			
Euro. efficiency [%]	97.7			
Battery charge/discharge efficiency [%]	98.5 / 97.5			
Degree of protection	IP65			
Operating temperature range [°C]	-35 ~ +60 (Derating above +45)			
Max. operation altitude [m]	< 3000			
Relative humidity [%]	0 ~ 100			
Typical noise emission [dB]	< 35	< 35	< 45	< 45
Storage temperature [°C]	-40 ~ +70			
Dimensions (WxHxD) [mm]	503 x 503 x 199			
Net weight [kg]	30			
Cooling concept	Natural cooling	Natural cooling	Nature cooling	Smart cooling
Communication interfaces	Meter (optional), External control RS485, Pocket WiFi (Optional: Pocket Lan / 4G), DRM, USB Upgrade, NTC (optional)			
POWER CONSUMPTION				
Internal consumption (night) [W]	< 40W for standby, < 5W for idle			
STANDARD				
Safety	EN / IEC62109-1 / -2			
EMC	EN61000-6-1 / 2 / 3 / 4; EN61000-3-2 / 3 / 11 / 12			
Certification	VDE4105, G99, G98, AS4777, EN50549, CEI 0-21, IEC61727, PEA / MEA, NRS-097-2-1, RD1699, TOR			